

Product Data Sheet

Hydroxyethyl Methyl Cellulose

MHEC MH60M

CAS No : 9032-42-2

MHEC MH60M is Hydroxyethyl Methyl Cellulose,also named as HEMC MH60M, Methyl Hydroxyethyl Cellulose,which is designed to enhance the quality and processing characteristics of construction materials such as tile adhesives and dry mix mortar,plasters,ceramic etc. it can increase good workability and good water retention ,excellent open time, slip resistance, impact resistance, adhesion and shear strength.

Specification

| | |
|----------------------------------|---------------------------|
| Physical form | White to off-white powder |
| Moisture | Max.6% |
| PH | 4.0-8.0 |
| Viscosity Brookfield 2% solution | 24000-36000mPa.s |
| Viscosity NDJ 2% solution | 48000-72000mPa.S |
| Ash content | Max5.0% |
| Mesh size: | 99% pass 100mesh |

Packing:

Packed in multi-ply paper bags with polyethylene inner layer, containing25 kgs; palletized & shrink wrapped.

Storage:

Store it in a cool, dry place below 30°C and protected against humidity and pressing, since the goods is thermoplastic, storage time should not exceed 36 months.

Safety notes:

The above data is in accordance with our knowledge, but don't absolve the clients carefully checking it all immediately on receipt. To avoid the different formulation and different raw materials, please do more testing before using it.